

Manure Management



The DT Roller Press is manufactured with heavy duty construction for longevity and strength against the most demanding applications. The press rolls are designed with advanced rubber roller vulcanization and are each individually driven to prevent slippage and stalling from large objects. Our DT Roller Press also has reinforced backing on the screen roller for added strength as well as a remote grease bank.



DARITECH 34", 48", 72" & 96" 2 Roller Press

- High production press
- Designed for use with two DT360's or DT-X
- Air bag to create a dryer product
- Expected dry matter 22-26%
- Heavy duty oversized bearings and shafts



DARITECH 22" & 42" 4 Roller Press

- Designed for use with DT360 or DT-X
- Individual air bag pressure to control dryness and feed speed between sets of rollers
- Expected dry matter 30-34%
- · Product usable as green bedding
- Heavy duty oversized bearings and shafts

DARITECH 24" 2 Roller Press

- Designed for use with a screw press separator to reduce screen wear on the separator and create dry matter suitable for green bedding or compost
- Expected dry matter 33-38%
- Air bag press to create a dryer product
- Heavy duty oversized bearings and shafts

DARITECH 34" 2 Roller Press (weighted)

- Designed for use with a DT360 Rotary Screen
 Separator or smaller dairies with a DT-X Separator
- Economical design
- Counter weight press design
- Expected dry matter 16-20%

DARITECH 48" 6 Roller Press

- Designed for use with DT360 or DT-X
- Individual air bag pressure to control dryness and feed speed between sets of rollers
- Expected dry matter 33-35%
- Product usable as green bedding
- Heavy duty oversized bearings and shafts

Daritech, Inc., offers a variety of roller press options to fit the press needs on your dairy. Call for specifications on your application needs.











Daritech, Inc 8540 Benson Road Lynden, WA 98264 Toll Free: 800-701-3632 Phone: 360-354-6900